


GE774° Ionizing Point™

Single point ionizer for spot neutralization!

What Is The **GETT4** Ionizing Point?

EXAIR's Gen4 Ionizing Point is a compact, single point ionizer ideal for winding, rewinding or slitting operations. It can also be mounted through a duct to neutralize static charges due to moving air or materials.

The shockless Gen4 Ionizing Point delivers a high concentration of positive and negative ions for fast static decay. It can neutralize any surface within 2" (51mm).



GET14 Ionizing Point Performance

	Distance	e From Charged Surface	
	0.50" (13mm)	1" (25mm)	2" (51mm)
Dissipates 5kV (seconds)	0.12	0.18	0.24

Applications

- Winding
- Rewinding
- Slitting
- · Neutralizing ducted air

Advantages

- Electromagnetically shielded high voltage cable • Replaceable emitter point
- cable protects against abrasion, cuts
- · Integrated ground design requires no separate ground connection
- Low cost
- Armored high voltage Rapid static decay
 - **Shockless**
 - · Non-radioactive
 - Compact

GET14 Ionizing Point Specifications

The Gen4 lonizing Point can be machine or

duct mounted.

EXAIR Model 7960 or 7961 Gen4 Power Supply (5kV) is required for Ionizing Point operation. See page 129 for details.

Certifications: The Gen4 Ionizing Point and Gen4 Power Supply are UL Component Recognized to U.S. and c**FL**°us Canadian safety standards, and are CE and RoHS CE compliant.

Electrical: For use with 5 kVrms, 5 milliamperes (max.) power supply.

Electrical Hazard: Shockless (less than 40 microamperes short circuited).

Do not use near flammable materials or gases.

Materials of Construction: Metal Parts: Stainless Steel Plastic Parts: UL rated 94 HB **Emitter:** Stainless Steel

Maximum Ambient Temperature: 165°F (74°C)

Model # 8199



The Model 8299 Gen4 **Ionizing Point System** includes the Gen4 **Ionizing Point and Model** 7960 Gen4 Power Supply.

<i>GE</i> 714 lonizing Point		
Description		
Gen4 Ionizing Point Only includes 5' (1.52m) shielded cable*		
Gen4 Ionizing Point System (see detail above)		

* For special length cables, please contact the factory.

Accessories and Components		
Model#	Description	
7960	2 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)	
7961	4 Outlet Selectable Voltage Gen4 Power Supply (115V, 230V, 50/60Hz)	
7905	Static Meter	